

08-10-00

A

Please type a plus sign (+) inside this box → ☐PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))	Attorney Docket No.	M10 25086 US
	First Inventor or Application Identifier	Said Karbassi et al
	Title	Flow Sensor Package
	Express Mail Label No.	EL288090437US

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing)	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 15] (preferred arrangement set forth below) - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure	6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 3]	ACCOMPANYING APPLICATION PARTS
4. Oath or Declaration [Total Pages 4] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed) i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	7. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s)) 8. <input checked="" type="checkbox"/> 37 C.F.R. § 3.73(b) Statement (when there is an assignee) <input checked="" type="checkbox"/> Power of Attorney 9. <input type="checkbox"/> English Translation Document (if applicable) 10. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations 11. <input type="checkbox"/> Preliminary Amendment 12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 13. <input type="checkbox"/> * Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired (PTO/SB/09-12) 14. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 15. <input checked="" type="checkbox"/> Other: Certificate of Mailing
* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).	

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____


Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label  or ☐ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name	ANDREW A. ABEYTA				
	Honeywell International Inc. PATENT TRADEMARK OFFICE				
Address	101 Columbia Road				
	POB 2245				
City	Morristown	State	NJ	Zip Code	07962
Country	U.S.A.	Telephone	602-313-3345	Fax	602-313-4559

Name (Print/Type)	Andrew A. Abeyta	Registration No. (Attorney/Agent)	39,582
Signature		Date	Aug. 9, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Docket No. M10 25086 US
Serial No. t.b.d.
Filed 08/09/00

Certificate of Mailing under 37 CFR 1.8

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to:

Box Application
Assistant Commissioner for Patents
Washington, D.C. 20231

on August 9, 2000
(Date)



Signature

Tessa Ricàr

Typed or printed name of person signing Certificate

Note: Each paper must have its own certificate of mailing, or this certificate must identify each submitted paper.

1. Utility Patent Application Transmittal;
2. Fee Transmittal for FY 2000, two copies;
3. Specification, fifteen pages;
4. Informal Drawings, four pages;
5. Declaration for Utility or Design Patent Application, executed, five pages;
6. Recordation Form Cover Sheet, two pages, two copies;
7. Assignment, executed, two pages;
8. Certificate of Mailing;
9. Return post card.

U.S. Express Mail Airbill No. EL288090437US

Burden Hour Statement: This form is estimated to take 0.03 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC, 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC, 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES PATENT

FLOW SENSOR PACKAGE

INVENTORS

Said Karbassi
2626 2nd Avenue
Monroe, Wisconsin 53566
Citizen of the United States of America

D. Joseph Maurer
785 South Silberman
Pearl City, Illinois 61062
Citizen of the United States of America

EXPRESS MAIL NO.: EL288090437US

FLOW SENSOR PACKAGE

BACKGROUND OF THE INVENTION

The present invention relates generally to a package for solid state electronic flow sensors
5 compatible with liquids or gases.

Typical flow sensors use solid state sensing elements that are not compatible with liquids.
Moreover, these devices require complicated packaging schemes to mount the sensing element
and to protect that element from the fluid passing through the flow sensor package.

10 A packaging scheme is known for a pressure gauge such that the pressure gauge can be
used to detect the pressure of either a liquid or a gas. The package of this pressure gauge
includes a solid state pressure sensing element and elastomeric seals. The pressure gauge detects
any change in pressure of a fluid. One of the elastomeric seals is conductive so as to connect
15 signals from the solid state pressure sensing element to electrical leads that exit the housing of the
pressure gauge. This type of pressure gauge is shown in U.S. Pat. No. 5,184,107 issued to Dean
J. Maurer on Feb. 2, 1993. This pressure gauge, however, is not a flow sensor and, therefore, is
not in the fluid channel.

20 The present invention integrates a pressure sensing element and a restriction into a low-
cost, highly-manufacturable flow sensor package. This packaging arrangement exposes the
pressure sensing element to the gas or fluid flow but protects the pressure sensing element from
the gas or fluid without the need for other protective devices.

BRIEF SUMMARY OF THE INVENTION

The following summary of the invention is provided to facilitate an understanding of some of the innovative features unique to the present invention and is not intended to be a full description. A full appreciation of the various aspects of the invention can be gained by taking the
5 entire specification, claims, drawings, and abstract as a whole.

In accordance with one aspect of the present invention, a flow sensor package comprises a housing, a sensing element, a restriction, and an elastomeric seal. The housing has an inlet port, an outlet port, and first and second channels between the inlet port and the outlet port. The
10 sensing element is in the first channel. The restriction is in the second channel. The elastomeric seal engages the sensing element so as to prevent flow of a gas or fluid through the first channel.

In accordance with another aspect of the present invention, a flow sensor package comprises a housing, a sensing element, a restriction, and an elastomeric seal. The housing has an
15 inlet port, an outlet port, and first and second channels between the inlet port and the outlet port. The sensing element is in the first channel. The restriction is in the second channel, and permits flow of a liquid through the inlet port, the second channel, and the outlet port. The sensing element senses a pressure drop across the restriction. The elastomeric seal engages the sensing element so as to prevent flow of a liquid through the first channel.

In accordance with yet another aspect of the present invention, a method of determining flow rate through a flow conductor comprises the following steps: creating a pressure drop within a housing; sensing the pressure drop, preferably using a sensing element mounted within the housing; sealing the sensing element within the housing using a seal; and communicating a
25 signal from the sensing element through the seal to an exterior of the housing.

The novel features of the present invention will become apparent to those of skill in the art upon examination of the following detailed description of the invention or can be learned by practice of the present invention. It should be understood, however, that the detailed description of the invention and the

PATENT
M10-25086

specific examples presented, while indicating certain embodiments of the present invention, are provided for illustration purposes only because various changes and modifications within the scope of the invention will become apparent to those of skill in the art from the detailed description of the invention and claims that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying figures, in which like reference numerals refer to identical or functionally-similar elements throughout the separate views and which are incorporated in and form part of the specification, further illustrate the present invention and, together with the detailed description of the invention, serve to explain the principles of the present invention.

FIGS . 1a and 1b are block diagrams of a flow system incorporating a flow sensor in accordance with the present invention; and

FIG. 2 illustrates a cross sectional side view of the flow sensor of FIG. 1a and 1b in additional detail.

FIG. 3 illustrates a block diagram of an alternate embodiment of a flow system incorporating a flow sensor in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

As shown in FIG. 1a, a flow sensor package 10 includes a housing 12 that can be fabricated from a suitable material, such as plastic, and that has an inlet port 14, an outlet port 16, a lead 18a, and first and second channels 20, 21, and third and fourth channels 22, 23. In a preferred embodiment, the first and second channels 20, 21 are parallel to one another and communicate with the inlet port 14 and the outlet port 16 by way of the third and fourth channels 22, 23. The inlet port 14 is adapted to receive a fluid such as a liquid, and the outlet port 16 can be adapted to discharge the fluid from the flow sensor package 10. The lead 18a is coupled to a measuring apparatus 26 such as, but not limited to, a microprocessor, a meter, etc.

The second channel 21 has a restriction 28. Restriction 28 can be a Venturi configuration (as shown in FIG. 3), which greatly increases velocity but can also reduce pressure and which can be adjusted. Alternatively, the restriction 28 can be provided by narrowing the second channel 21 with respect to the first channel 20 and the third and fourth channels 22, 23 rather than incorporating a restriction 28. The first channel 20 has a pressure sensing element 30 that can be, for example, a strain sensor (e.g., capacitive), a stress sensor or a piezoresistive pressure transducer with a conductive elastomeric seal as described in U.S. Pat. No. 5,184,107 issued to Dean J. Maurer on Feb. 2, 1993, the disclosure of which is incorporated herein by reference although those skilled in the art will realize that other types of seals can be substituted depending on the application. As discussed further below, the pressure sensing element 30 is adapted to detect a pressure change created by the restriction 28 and is coupled to the lead 18a as shown in detail in U.S. Pat. No. 5,184,107. Similarly, those skilled in the art will realize that other sensing elements can be used in accordance with the teaching of the present invention such as, for example, a temperature sensing element.

As described above, the inlet port 14 receives a fluid, and the outlet port 16 discharges the fluid from the flow sensor package 10. However, as further discussed below and as shown in FIG. 1b, the flow sensor package 10 is bidirectional. In either case, the fluid moves through the flow sensor package 10 by flowing through the restriction 28 in the second channel 21. The

restriction 28 in the second channel 21 creates a pressure drop from one face of the pressure sensing element 30 to the other in the first channel 20. The pressure sensing element 30 and a pair of elastomeric seals (discussed below in connection with FIG. 2) prevent flow of the fluid through the first channel 20 and measures the pressure drop created by the restriction 28.

5 Accordingly, the pressure sensing element 30 sends a signal, for example, a voltage, to the measuring apparatus 26 through the lead 18a.

As exemplified in FIG. 1a, the fluid flows through the flow sensor package 10 in a clockwise orientation by entering through the inlet port 14 and exiting through the outlet port 16.

10 Alternatively, as noted above, the flow sensor package 10 can be bidirectional. Accordingly, as exemplified in FIG. 1b, the fluid flows through the flow sensor package 10 in a counter-clockwise orientation by entering through the outlet port 16 and exiting through the inlet port 14. In particular, the outlet port 16 receives the fluid, and the inlet port 14 discharges the fluid from the flow sensor package 10.

15 As shown in FIG. 2, one embodiment of the flow sensor package 10 generally includes the housing 12, the first and second channels 20, 21, the third and fourth channels 22, 23, the restriction 28, the pressure sensing element 30, and an elastomeric seal 32, which has a conductive path to a lead 18a in the manner shown, for example, in aforementioned U.S. Pat. No.
20 5,184,107. The housing 12 has an alignment well 34 in the first channel 20 between the inlet port 14 the outlet port 16. Although not necessary, because of the third and fourth channels 22, 23, the first and second channels 20, 21 are shown in parallel across the inlet port 14 and the outlet port 16.

25 The housing 12 is formed by two portions: a base 36 carrying the alignment well 34, the third channel 22, and the inlet port 14, and a cover 38 carrying the outlet port 16 and the fourth channel 23. Those skilled in the art will realize that the housing can be integrally molded or can have additional components. The alignment well 34 is configured to support the elastomeric seal 32, another elastomeric seal 40, and the pressure sensing element 30. The pressure sensing

PATENT
M10-25086

element 30 is positioned between the elastomeric seals 32, 40 within the alignment well 34 in order to prevent flow through the first channel 20. The elastomeric seal 32, which has a conductive path from the pressure sensing element 30 to the lead 18a that extends outside of the housing 12 to couple to the measuring apparatus 26, rests in the alignment well 34 of the base 36.

5 The pressure sensing element 30 is oriented so that it is electrically coupled to the conductive elastomeric seal 32 and so that the elastomeric seal 40 rests on the pressure sensing element 30. The pressure sensing element 30 can be, but is not limited to, a square chip as described in U.S. Pat. No. 5,184,107 issued to Dean J. Maurer on Feb. 2, 1993. The configuration between the conductive elastomeric seal 32, the elastomeric seal 40, and the pressure sensing element 30 is
10 described in detail in U.S. Pat. No. 5,184,107. The first channel 20 is sealed at the interface between the base 36 and the cover 38 by the elastomeric seals 32, 40 that can be, but are not limited to, silicone, ethyl-propylene (EPDM), nitrile, viton, butadiene, combinations thereof, etc. The second channel 21 is sealed at the interface between the base 36 and the cover 38 with elastomeric seals 44 that can be the same material referred to above. The elastomeric seals 32,
15 40, 44 prevent leakage out of the flow sensor package 10. The cover 38 can be arranged to snap onto the base 36 to form a complete flow sensor package 10, which allows a fluid to enter through the inlet port 14, to flow through the restriction 28, and to exit through the outlet port 16.

20 A fluid enters the flow sensor package 10 through the inlet port 14 carried by the base 36. The fluid flows through the restriction 28 in the second channel 21, which allows the fluid a bypass path through the flow sensor package 10. The elastomeric seal 44 prevents leakage of the fluid from the second channel 21, thereby allowing the restriction 28 to create a pressure change across the pressure sensing element 30. Accordingly, the pressure sensing element 30, which
25 prevents flow of the fluid through the first channel 20, measures the pressure change across the pressure sensing element 30 and provides an electrical output signal to the conductive elastomeric seal 32. The conductive elastomeric seal 32 is electrically coupled to the measuring apparatus 26 through the lead 18a so that the signal from the pressure sensor element 30 reaches the measuring

apparatus 26. Along with the elastomeric seal 40, the conductive elastomeric seal 32 prevents leakage of the fluid from the first channel 20.

With this arrangement, the pressure sensing element 30 is integrated with the restriction 28 in the housing 12 and is sealed by elastomeric seals 32 to form a low-cost, highly-manufacturable flow sensor package 10 to measure the flow rate of a fluid.

Certain modifications of the present invention have been discussed above. Other modifications will occur to those practicing in the art of the present invention. For example, as illustrated in the drawings, the inlet port 14 and the outlet port 16 have axes that form right angles with respect to the axes of the first and second channels 20, 21. However, the housing 12 can be arranged so that the inlet port 14 and the outlet port 16 have axes that are parallel to the axes of the first and second channels 20, 21. Further, for example, those skilled in the art will realize that channels 20 and 21 can be reversed so that the channel 20 is in the center of the drawings shown in FIGS. 1a, 1b, and 2 (i.e., the sensing element 30 will be in what is shown as channel 21 in FIG. 2 with appropriate changes made to the configuration of flow sensor package 10). Also, sensing element 30 can be placed in any variety of locations, such as, for example, in channel 22 to the left of channel 21 in FIG. 2 (perpendicular to the flow).

Referring to FIG. 3, there is shown an alternate embodiment of a flow system incorporating a flow sensor in accordance with the present invention. In the embodiment shown in FIG. 3, the first and second channels 20, 21 are not parallel to one another. The first and second channels 20 and 21 communicate with the inlet port 14 and the outlet port 16 by way of the third and fourth channels 22, 23. The inlet port 14 is adapted to receive a fluid such as a liquid, and the outlet port 16 can be adapted to discharge the fluid from the flow sensor package 10. Restriction 28 is shown in a Venturi configuration (bypass flow channel), which greatly increases velocity but can also reduce pressure and which can be adjusted. The lead 18a is coupled to a measuring apparatus 26 (not shown) such as, but not limited to, a microprocessor, a meter, etc.

PATENT
M10-25086

The embodiments and examples set forth herein are presented to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. Those skilled in the art, however, will recognize that the foregoing description and examples have been presented for the purpose of illustration and example only. Other variations and modifications of the present invention will be apparent to those of skill in the art, and it is the intent of the appended claims that such variations and modifications be covered. The description as set forth is not intended to be exhaustive or to limit the scope of the invention. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims. It is contemplated that the use of the present invention can involve components having different characteristics. It is intended that the scope of the present invention be defined by the claims appended hereto, giving full cognizance to equivalents in all respects.

CLAIMS

The embodiments of an invention in which an exclusive property or right is claimed are defined as follows:

1. A flow sensor package comprising:
 - a housing having an inlet, an outlet, and first and second channels in communication with the inlet and the outlet;
 - a sensing element in the first channel;
 - 5 a restriction in the second channel; and
 - a seal engaging the sensing element so as to prevent flow of a fluid past the sensing element.
2. The flow sensor package of Claim 1, wherein the housing includes a base and a cover.
3. The flow sensor package of Claim 2, wherein the seal comprises a pair of elastomeric seals, wherein the sensing element is captured between the elastomeric seals, and wherein the elastomeric seals are arranged to prevent leakage between the base and cover.
4. The flow sensor package of Claim 1, wherein the seal comprises a pair of elastomeric seals, and wherein the sensing element is captured between the elastomeric seals.
5. The flow sensor package of Claim 1, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.
6. The flow sensor package of Claim 1, wherein the fluid is a liquid or a gas.
7. The flow sensor package of Claim 1, wherein the inlet, the outlet, and the second channel are arranged to permit a flow of the fluid through the housing between the inlet and the outlet, and wherein the sensing element is arranged to sense a pressure change across the restriction.

PATENT
M10-25086

8. The flow sensor package of Claim 7, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.

9. The flow sensor package of Claim 1, wherein the inlet, the outlet, and the second channel are arranged to permit a bidirectional flow of the fluid through the housing between the inlet and the outlet, and wherein the sensing element is arranged to sense a pressure change across the restriction.

5

10. The flow sensor package of Claim 9, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.

11. A flow sensor package comprising:

a housing having an inlet, an outlet, and first and second channels in communication with the inlet and the outlet;

a sensing element in the first channel;

5

a restriction in the second channel, wherein the restriction permits flow of a liquid through the inlet, the second channel, and the outlet; and

a seal engaging the sensing element so as to prevent flow of the liquid past the sensing element, wherein the sensing element senses a pressure change across the restriction.

12. The flow sensor package of Claim 11, wherein the housing includes a base and a cover.

13. The flow sensor package of Claim 12, wherein the seal comprises a pair of elastomeric seals, wherein the sensing element is captured between the elastomeric seals, and wherein the elastomeric seals are arranged to prevent leakage of the liquid between the base and cover.

14. The flow sensor package of Claim 11, wherein the seal comprises a pair of elastomeric seals, and wherein the sensing element is between the elastomeric seals.

15. The flow sensor package of Claim 11, wherein the inlet, the outlet, and the second channel are arranged to permit a flow of the liquid through the housing between the inlet and the outlet.

16. The flow sensor package of Claim 15, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.

17. The flow sensor package of Claim 11, wherein the inlet, the outlet, and the second channel are arranged to permit a bidirectional flow of the liquid through the housing between the inlet and the outlet.

18. The flow sensor package of Claim 17, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.

19. The flow sensor package of Claim 11, wherein the seal has a conductive path from the sensing element to a lead, and wherein the lead extends outside of the housing.

20 A method of determining flow rate through a flow conductor comprising the following steps of:
creating a pressure change within a housing;
sensing the pressure change using a sensing element mounted in communication with the
5 housing;
sealing the sensing element within the housing using a seal; and
communicating a signal from the sensing element through the seal to an exterior of the housing.

21. The method of Claim 20, wherein the sealing step comprises the step of sealing leakage between a base and a cover of the housing.

PATENT
M10-25086

22. The method of Claim 20, wherein the sealing step comprises the step of sealing the sensing element between a pair of elastomeric seals which capture the sensing element therebetween.

FLOW SENSOR PACKAGE

ABSTRACT OF THE DISCLOSURE

5 A flow sensor package with a housing, a pressure sensing element, a restriction, and an elastomeric seal. The housing has a base, a cover, an inlet port, an outlet port, and first and second channels. The first and second channels are in parallel between the inlet port and the outlet port. The pressure sensing element is in the first channel and the restriction is the second channel. The elastomeric seal engages the pressure sensing element to prevent flow of a fluid, which may be a liquid, through the first channel. The elastomeric seal has a conductive path from
10 the pressure sensing element to a lead, which extends outside the housing.




FIG. 1b




FIG. 2




FIG. 3

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

+

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	M10 25086 US
	First Named Inventor	Said Karbassi et al.
	COMPLETE IF KNOWN	
	Application Number	09 / t.b.d.
	Filing Date	AUGUST 9, 2000
	Group Art Unit	t.b.d.
	Examiner Name	t.b.d.

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FLOW SENSOR PACKAGE

the specification of which
☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) [] as United States Application Number or PCT International

Application Number [] and was amended on (MM/DD/YYYY) [] (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

+

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. ☒ Customer Number 000128 →

Place Customer Number Bar Code Label here

OR
☐ Registered practitioner(s) name/registration number listed below

Name	Registration Number	Name	Registration Number
Andrew A. Abeyta	39,582		
Anthony Micologos	29,677		


☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number 000128 OR ☒ Correspondence address below

Name	Andrew A. Abeyta				
Address	Honeywell International Inc.				
Address	101 Columbia Road, POB 2245				
City	Morristown	State	NJ	ZIP	07962
Country	USA	Telephone	602-313-3345	Fax	602-313-4559

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])		Family Name or Surname					
Said		Karbassi					
Inventor's Signature				Date	8/7/2010		
Residence: City	Nashua	State	NH	Country	USA	Citizenship	U.S.A.
Post Office Address	D6 Black Oak Dr.						
Post Office Address							
City	Hillsborough	State	NH	ZIP	03062	Country	USA

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → +

PTO/SB/02A (3-97)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S)
Supplemental Sheet
Page 3 of 4

Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
D. Joseph				MAUREL Maurer			
Inventor's Signature	D. Joseph Maurer			8/7/00		Date	
Residence: City	Pearl City	State	IL	Country	U.S.A.	Citizenship	U.S.A.
Post Office Address	785 South Silberman						
Post Office Address							
City	Pearl City	State	IL	ZIP	61062	Country	U.S.A.
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/02C (3-97)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.


DECLARATION

REGISTERED PRACTITIONER INFORMATION (Supplemental Sheet)

Name	Registration Number	Name	Registration Number
Andrew A. Abeyta	39,582		
William C. Anderson	28,147		
Virginia Szigeti Andrews	29,039		
Melanie L. Brown	31,592		
Curtis B. Brueske	33,839		
Marie Collazo	44,085		
Roger H. Criss	25,570		
Robert Desmond	38,450		
John Donofrio	32,339		
Anthony E. Ebert	41,727		
Felix Fischer	31,614		
Jay P. Friedenson	22,465		
Kris T. Fredrick	42,554		
William J. Iseman	27,138		
Albert K. Kau	40,672		
Mary Ann G. Lemere	32,160		
Robert B. Leonard	33,946		
Ian D. MacKinnon	34,660		
Paul L. Marshall	31,178		
Anthony Miologos	29,677		
Larry J. Palguta	29,575		
Charles Rubow	24,631		
John G. Shudy, Jr.	31,214		
John A. Squires	37,451		
Ephraim Starr	41,325		
Jeanne C. Suchodolski	34,936		
Colleen Szuch	32,126		
Leslie Weise	36,305		
Loria B. Yeadon	35,063		
William Zak, Jr.	38,668		

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Scanned copy is best available.

☒ There are 4 sheets of drawings